



# CALI660

## Safelatch™ 2-way 6.5" ceiling speaker with Twist-Fix™ grill

### Highlights:

---

- Secure Safelatch™ system
- Ceramic terminal block
- Excellent off-axis performance (up to 145°)
- Unique TwistFix™ grill design
- Borderless grill design
- Rotary switch for 16W, 32W, 64W and an 8 Ohm tapping
- Shallow built-in depth (120 mm)

The CALI660 is a 2-way ceiling speaker with rear dome, constructed using a 6.5" cone driver, combined with a coaxially mounted 1" soft dome tweeter which is fitted with a phase plug for excellent off axis performance up to 145°.

The 2-way construction combination with metal rear-dome guarantees premium performance for demanding applications. A continuous power handling of 60 Watt (RMS) and maximum power handling of 120 watt is achieved, while fitted with a rotary switch for tapping of the 100V line transformer with tapings for 60W, 30W, 15W and an 8 Ohm bypass connection.




### Impedance:

---



### Voltage:

---



## System specifications:

---

Max. Power		120 W
RMS Power		60 W
Sound Pressure (Max. W/1m)	@ 100 V	106 dB
Sensitivity (1W/1m)		86 dB
Dispersion	Conical	145°
Frequency	Response ( $\pm 3$ dB)	90 Hz - 20 kHz
	Range (-10 dB)	65 Hz - 20 kHz
Line Transformer Tappings	1	60 W / 167 $\Omega$
	2	30 W / 333 $\Omega$
	3	15 W / 667 $\Omega$
Speaker type		2-way coaxial
Connection		Ceramic screw terminal with link through

## Product Features:

---

Cut-out measurement	220 mm ( $\emptyset$ )
Dimensions	242 x 120 mm ( $\emptyset$ x D)
Built-in depth	120 mm
Operating temperature	-20 °C ~ 60 °C
Construction	ABS and powder coated steel
Mounting	SafeLatch™ mounting system