

## Highlights:

---


- EN50399 CPR Euroclass Cca-s1b,d1,a1
- 24 AWG (0.20 mm<sup>2</sup>) thin and dense stranded conductors
- Individual foil shielding with drain wire

## Product information:

---

The CSB224-CCA is a high quality stereo balanced signal cable compliant to Cca standards of the Construction products regulations (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its improved fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The conductor section consists of two individually jacketed pairs which are surrounded by one outer jacket, allowing stereo balanced signal transfer over one single cable. Each individual pair consists of a 24 AWG stranded conductor with an aluminum foil shielding and drain wire. The highly effective shielding offers excellent immunity against noise and interference caused by external devices. The stranding keeps the cable flexible and easy to handle.



CSB224 • EN50399 CPR Euroclass Cca-s1b,d1,a1



## Certification:

---

## Properties:

---




## Inner Conductors:

---



## Shielding:

---



## Usage:

INSTALL

## Product Features:

Application	AV & IT
Series	Contractor Series

## Physical Characteristics:

EN50399 CPR Euroclass	Cca-s1b,d1,a1		
Inner conductor	Insulation	Colours	Red / Blue White / Red
Outer jacket	Colours	Black	
	Material	Polyolefin 11 mm (Ø)	
Type of cable	24 AWG Microphone cable		
Inner conductor	Material	BC 25 x 0.1 mm (Ø) (OFC)	
	Section	0.20 mm <sup>2</sup>	
	American Wire Gauge	24 AWG	
	Number of conductors	2	
	Conductor twisting	Yes	


## Mechanical Characteristics:

Temperature range	Mobile installation	- 5 °C till + 80 °C
	Fixed installation	- 15 °C till + 80 °C

## Electrical Characteristics:

Max. conductor	DC resistance	85 (Ω / Km)
Dielectric strength	500 (kV / 1 min. DC)	
Rated voltage	100 V	

## Cross sections:



## Variants:

- CSB224-CCA/1 - 100 m wooden reel
- CSB224-CCA/3 - 300 m wooden reel