

DVI-OUT4-F32

4-Channel DVI Output Card

| DVI



DVI-OUT4-F32 is a four-channel DVI output card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The DVI-OUT4-F32 outputs four DVI signals from the chassis

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel) DVI Rev. 1.0



TECHNICAL SPECIFICATIONS

PORTS: 4 DVI-D on Molex 24-pin (F) connectors

BANDWIDTH PER

CHANNEL:

1.65Gbps

TOTAL BANDWIDTH: 4.95Gbps

MAXIMUM RANGE: 15m (49ft)

3D PASS THROUGH: Not supported

POWER

CONSUMPTION:

3W

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE: -40° to +70°C (-40° to 158°F)

10% to 90%, RHL non-condensing

STANDARD

HUMIDITY:

COMPLIANCE:

DVI 1.0

SAFETY

REGULATORY

CE, FCC

COMPLIANCE:

ENVIRONMENTAL REGULATORY

COMPLIANCE:

Complies with appropriate requirements of RoHs and WEEE

PRODUCT DIMENSION: 22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H

PRODUCT WEIGHT: 0.2kg (0.5lbs) approx

SHIPPING

27.00cm x 23.00cm x 5.60cm (10.63" x 9.06" x 2.20") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.4kg (0.9lbs) approx