

Hohe Auflösung



WU630



EH400



DH1020



EH500

	WU630	EH400	DH1020	EH500
Auflösung	WUXGA 1920 x 1200	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	6200 Centre Lumen (6000 ANSI)	4000 Lumen	3400 Lumen	4700 ANSI Lumen
Kontrastverhältnis	4400:1 (1150:1 full on / full off)	22,000:1	22,000:1	10,000:1
Betriebsgeräusch (Eco Modus)	35dB (Eco Modus), 39dB (Bright Modus)	28dB	28dB	28dB
Gewicht (kg)	13.9	2.41	2.17	3,6
Lampenlebensdauer ² (hrs)	2000/1500 Eco/Bright	7000/6500/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy de	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy de	4000/3000/2500 Eco+/Dynamic/Bright
Maße	453 x 390 x 206mm (ohne Überstände)	298 x 230 x 96.5	298 x 230 x 96.5	326 x 254 x 104
Bildgröße	50" - 300" diagonal (108 x 67cm - 646 x 404cm)			0,72 - 8,67m (28,41" - 341,28") Diagonal 16:9
Projektionsverhältnis	0,75 bis 5,50 (abhängig vom Objektiv)	1.47 - 1.63:1	1.48 - 1.62:1	1,59 - 1,91:1
Zoom	motorisiert	1,1-fach manuell	1,1-fach manuell	1,2-fach manuell
Keystone Korrektur	Vertikal ±20°	± 40° vertikal	± 40° vertikal	± 30° Vertikal
Verbindungen	HDMI V.1.3, DVI-D, VGA (YPbPr), 5 BNC, Composite, VGA Out, RJ45, RS-232, 12V Trigger	2x HDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (5V-1A)	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB Service	2 x HDMI, DisplayPort, 2 x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RC/A/3,5mm), Audio Out 3.5mm, 3.5mm, VGA Out, RJ45, RS232, USB (Maussteuerung), +12V Trigger, 3D-Sync
Optionales Wireless	Nein	Ja	Ja	Ja
Lautsprecher (Watt)	-	2	2	3
Tasche	Nein	Nein	Nein	Ja
Features	5 Wechsellobjektive, motorisierter Lens Shift, 360° Betrieb			Einfacher Lampenwechsel, Crestron RoomView®, PJ-Link

Hohe Auflösung



DH1009i



EH400+



DH401



ZH400UST

	DH1009i	EH400+	DH401	ZH400UST
Auflösung	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	3200 Lumen	4000 Lumen	4000 ANSI Lumen	4000 Lumen
Kontrastverhältnis	22,000:1	22,000:1	15,000:1	100,000:1
Betriebsgeräusch (Eco Modus)	26dB	29dB	32dB	30/ 35dB (Eco/ Bright mode)
Gewicht (kg)	2.38	2.52	2.99	5.6
Lampenlebensdauer ² (hrs)	8000/6000/5000 Dynamic/Eco/Bright	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy de	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	20000 Bright
Maße	298 x 230 x 96.5	298 x 230 x 96.5	314 x 224 x 114	382 x 310 x 124mm
Bildgröße				2.2 - 2.59m (87" - 102") diagonal 16:9
Projektionsverhältnis	1.48 - 1.62:1	1.13 - 1.47	1.4 - 2.24:1	0.25:1
Zoom	1,1-fach manuell	1,3-fach manuell	1,6-fach manuell	1,0x fix
Keystone Korrektur	± 40° vertikal	± 40° vertikal	± 40° vertikal	±15° V, ±15° H
Verbindungen	2x HDMI (1.4a 3D support) + MHL v2.1, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB-A Power (1A)	2x HDMI (1.4a 3D support) + MHL v2.1, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (1A)	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	2x HDMI V.1.4a, 2x VGA, 2x 3.5mm Audio, VGA-out, 3.5mm Audio out, RJ45, RS232, 12v Trigger, Mini USB (service)
Optionales Wireless	Ja	Ja	Ja	Ja
Lautsprecher (Watt)	10	10	10	10W
Tasche	Nein	Nein	Nein	Nein
Features				1080p Auflösung, Ultrakurzstrecke, DuraCore Laser

Hohe Auflösung

Breitbild



ZH400USTi



ZW400UST



ZW400USTi



ZH400USTi

	ZH400USTi	ZW400UST	ZW400USTi	ZH400USTi
Auflösung	1080p 1920 x 1080	WXGA 1280 x 800	WXGA 1280 x 800	1080p 1920 x 1080
Brightness ¹ (Bright mode)	4000 ANSI lumens	4000 ANSI lumens	4000 ANSI lumens	4000 ANSI lumens
Kontrastverhältnis	100,000:1	100,000:1	100,000:1	100,000:1
Betriebsgeräusch (Eco Modus)	30dB	30dB	30dB	30dB
Gewicht (kg)	5.6	5.6	8.8	5.6
Lampenlebensdauer ² (hrs)	0 Bright	0 Bright	0 Bright	0 Bright
Maße	382 x 310 x 124mm	382 x 310 x 124mm	382 x 310 x 124mm	382 x 310 x 124mm
Bildgröße	2.2 - 2.59m (87" - 102") diagonal 16:9	85"~115" diagonal 16:10	85"~115" diagonal 16:10	2.2 - 2.59m (87" - 102") diagonal 16:9
Projektionsverhältnis	0.25:1	0.27:1	0.27:1	0.25:1
Zoom	1.0x fixed	1.0x fixed	1.0x fixed	1.0x fixed
Keystone Korrektur	±15° V, ±15° H	±15° V, ±15° H	±15° V, ±15° H	±15° V, ±15° H
Verbindungen	2x HDMI V.1.4a, 2x VGA, 2x 3.5mm Audio, VGA-out, 3.5mm Audio out, RJ45, RS232, 12v Trigger, Mini USB (service)	2x HDMI V.1.4a, 2x VGA, 2x 3.5mm Audio, VGA-out, 3.5mm Audio out, RJ45, RS232, 12v Trigger, Mini USB (service)	2x HDMI V.1.4a, 2x VGA, 2x 3.5mm Audio, VGA-out, 3.5mm Audio out, RJ45, RS232, 12v Trigger, Mini USB (service)	2x HDMI V.1.4a, 2x VGA, 2x 3.5mm Audio, VGA-out, 3.5mm Audio out, RJ45, RS232, 12v Trigger, Mini USB (service)
Optionales Wireless	Ja	Ja	Ja	Ja
Lautsprecher (Watt)	10W	10W	10W	10W
Tasche	Nein	Nein	Nein	Nein
Features	1080p resolution, ultra short throw, laser phosphor light engine	WXGA resolution, ultra short throw, laser phosphor light engine	WXGA resolution, ultra short throw, laser phosphor light engine	1080p resolution, ultra short throw, laser phosphor light engine