

900N

Stereo Power Amplifier (10 Watts per Channel)

| Speakers



The 900N is a high–performance power amplifier for balanced or unbalanced stereo audio signals. Either input can deliver a speaker output of 10 watts RMS power per channel into a 4Ω load

FEATURES

High Efficiency - Class D operation

S/N Ratio - 55dB

Controls - Volume knob, On LED

Special Note - Before turning on the 900N, make sure the volume is turned down to the minimum Compact Kramer TOOLS $^{\text{TM}}$ - 3 units can be rack mounted side-by-side in a 1U rack space with the

recommended rack adapter



TECHNICAL SPECIFICATIONS

INPUTS: 1 unbalanced stereo audio on RCA connectors; 1 balanced stereo audio on a

5-pin terminal block connector

OUTPUT: 1 stereo loudspeaker output on a 4-pin terminal block connector

OUTPUT POWER: 10W RMS per channel into a 4Ω load

OUTPUT MUSIC

35W RMS per channel into a 4Ω load

POWER:

BANDWIDTH (-3dB): 24kHz

S/N RATIO: 55dB

CONTROLS: Gain: -40dB to +19dB until the compression threshold

COUPLING: Input: AC; speakers out: DC

AUDIO THD + NOISE: 0.5% @1kHz

AUDIO 2nd 0.04% @1kHz

HARMONIC:

POWER 12V DC, 2.1A

CONSUMPTION:

INCLUDED Power supply, mounting bracket

ACCESSORIES:

PRODUCT 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

TROBOOT WEIGHT. U.Zkg (U.4103) approx

SHIPPING DIMENSION:

23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H

SHIPPING WEIGHT: 0.6kg (1.3lbs) approx

