

900xl

Stereo Power Amplifier (10 Watts per Channel)

| Speakers



The 900xl is a high–performance power amplifier for line level stereo audio signals. The unit accepts unbalanced audio signals on either of two RCA or 3.5mm connectors and delivers a speaker output of 10 watts RMS per channel into a 4Ω load

FEATURES

High Efficiency - Class D operation

S/N Ratio - 60dB

Control - Volume & input selection from front panel & RS-232

Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



TECHNICAL SPECIFICATIONS

INPUTS: 1 unbalanced stereo audio on a 3.5mm mini jack connector, 1 unbalanced stereo

audio on RCA connectors

OUTPUT: 1 stereo differential speaker output

OUTPUT POWER: $2x10W(4\Omega)$

INPUT SENSITIVITY: 460mV

OUTPUT MUSIC $2x40W (4\Omega)$

POWER:

BANDWIDTH (-3dB): 25kHz

S/N RATIO: 85dB @1kHz, 0dBu output

CONTROLS: Gain range: -14 to +32dB at high-gain; -21 to +20dB at low-gain

COUPLING: Input: AC; output: DC

AUDIO THD + NOISE: 0.6% @0dBu output

AUDIO 2nd HARMONIC:

12V DC, 2.0A

POWER CONSUMPTION:

OPERATING 0° to +40°C (32° to 104°F)

TEMPERATURE:

STORAGE -45° to +72°C (-49° to 162°F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

0.35% @0dBu output

INCLUDED Power supply

ACCESSORIES:

PRODUCT

DIMENSION:

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.0kg (0.0lbs) approx

SHIPPING 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.6kg (1.4lbs) approx

