



KRAMER

PT-110EDID

Computer Graphics Video over Twisted Pair
Transmitter with EDID



The PT-110EDID is a twisted pair transmitter for computer graphics video signals. It converts a computer graphics signal into a twisted pair signal that is converted back to a computer graphics video signal when used with a compatible receiver

FEATURES

Max. Resolution - WUXGA & 1080p

HDTV Compatible

EDID Capture - Copies and stores the EDID from a display device

Sync Polarity Settings - H & V switches for improved display compatibility with the CAT 5 outputs

System Range - Up to 100m (320ft). Greater distances possible depending on resolution and cable

Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5

Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other

Ultra Compact Pico TOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

INPUT:	1 VGA/UXGA on a 15-pin HD connector
OUTPUT:	1 RJ-45 LINE OUTPUT connector
RESOLUTION:	Up to WUXGA & 1080p
S/N RATIO:	69dB (worst case)
COUPLING:	AC
POWER CONSUMPTION:	12V DC, 320mA
INCLUDED ACCESSORIES:	Power supply
PRODUCT DIMENSION:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx
SHIPPING DIMENSION:	17.40cm x 12.00cm x 8.60cm (6.85" x 4.72" x 3.39") W, D, H
SHIPPING WEIGHT:	0.4kg (1.0lbs) approx

