



KRAMER

RC-54DL

12-button KNET™ Auxiliary Keypad with Knob and Displays (US)



The RC-54DL is a 12-button auxiliary keypad, with knob and LCD displays. Connected over KNET™ to master control keypad such as RC-74DL, the RC-54DL is ideal for serving as remote secondary keypad in classrooms, boardrooms or auditoriums, for convenient control of their multimedia devices

FEATURES

Back Lit & Label Capable Buttons - 6 RGB-color, tactile feedback, backlit buttons. Buttons are grouped in 2 groups, 4 buttons in 'SOURCES' group, and 2 buttons in 'DISPLAY' group

Custom Labeled, Removable Button Caps

Volume Control Knob with LEDs - Bi-directional rotary dialed digital knob for volume control, with 5 LED bar for visual volume level feedback

LCD Displays - 3 blue-color and 8 white-characters LCD displays, in 3 button groups, for programmed visual feedback indication and group configured labeling, such as knob control state of either audio or light level

2 K-NET™ Connectors - Connects to master room controller, and auxiliary keypads for remote keypad control

K-NET™ Single Link Connection - Provides a single keypad link cable-connectivity, carrying both power and keypad control communication information

Program Control - Program configuration with Kramer K-Config software

Keypad Lock-Out - Option for tampering prevention by locking and unlocking of the keypad buttons

Mini USB Port - To upload configuration files, set the K-NET™ ID number, and power the device during configuration

Mounting - In-wall, in standard 3 gang US wall junction boxes

Easy Installation - Fits to standard in-wall boxes for simple and cost-reducing installation



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|------------------------|--|
| PORTS: | 2 K-NET on terminal block connectors, 1 mini USB for programming |
| POWER CONSUMPTION: | 12V DC, 480mA |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power supply, label set, screwdriver |
| PRODUCT DIMENSION: | US: 16.20cm x 2.30cm x 11.43cm (6.38" x 0.91" x 4.50") W, D, H |
| PRODUCT WEIGHT: | US: 0.2kg (0.3lbs) approx |
| SHIPPING DIMENSION: | US: 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H |
| SHIPPING WEIGHT: | US: 0.7kg (1.4lbs) approx |



KRAMER

CONFIGURATIONS

| | |
|-----------------|--|
| RC-54DL(W) | US-size RC-54DL, White Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-54DL/JP(W) | US-size RC-54DL, White Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-54DL(G) | US-size RC-54DL, Gray Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-54DL/JP(G) | US-size RC-54DL, Gray Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-54DL(B) | US-size RC-54DL, Black Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-54DL/JP(B) | US-size RC-54DL, Black Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-54DL(BAL) | US-size RC-54DL, Brushed Aluminum Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-54DL/JP(BAL) | US-size RC-54DL, Brushed Aluminum Design Frame, PSU + Power cord, Label Set, Screwdriver |

