


**RGB VIDEO CABLE
RGB600**



Composite

OUTER DIAMETER

3 x Ø 6 mm

APPLICATIONS

High resolution RGB video connections, ideal for pre-cabling commercial and residential projects

<p>Inner Conductor</p>  <p>BARE COPPER</p>	<p>Shielding</p>  <p>BARE COPPER SPIRAL ALUMINUM FOIL</p>	<p>Compatible with</p>  <p>NEUTRIK BNC CONNECTOR NBNC75BFH6</p>	 <p>75 Ω</p>
--	--	---	--

Type of cable	RGB Coaxial video cable - 75 Ohm
Inner conductor	BC 20 x 0,12 mm
Inner conductor section	0,22 mm ²
Isolation	Foamed PE Ø 3,2 mm
Isolation colour	Red / Blue / Green
Number of conductors	3
Shielding	BC 56 x 0,12 mm - Spiral Aluminum foil
Shielding %	100%
Outer jacket	Flexible PVC
Outer jacket colour	Black
Outer jacket dimensions	3 x 6 mm Ø
Impedance	75 Ohm
American Wire Gauge	24 AWG


MECHANICAL SPECIFICATIONS

Temperature range	fixed installation	-40° C till +80° C
	flexible installation	-15° C till +60° C
Bending radius	fixed installation	6 x outer diameter
	flexible installation	8 x outer diameter

ATTENUATION SPECIFICATIONS

Attenuation (dB/100 ft.)	5 Mhz	10 Mhz	50 Mhz	100 Mhz	300 Mhz	500 Mhz	1 Ghz
RGB600	0,76	0,91	2,13	3,12	5,67	7,56	11.58
Attenuation (dB/100 m)							
RGB600	2.50	3,00	7,00	10,25	18,60	24,80	38,00

 Available Lengths: _____
100 m plastic reel



Video
BULK CABLES

