


SPEAKER CABLE



★★★★★

SPEAKER CABLE

Applications
Indoor use
High-quality installations over long distances

RZ SERIES

- RZ07**
- RZ15**
- RZ25**
- RZ40**



The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible jacket of PVC. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are “all-round” loudspeaker cables suited for all kinds of applications on loudspeaker level.

GENERAL SPECIFICATIONS

Cable model	RZ07	RZ15
Type of cable	Speaker cable	Speaker cable
Inner conductor	BC 10 x 7 x 0,12 mm	BC 20 x 7 x 0,12 mm
Inner conductor section	0,7 mm ²	1,5 mm ²
Number of conductors	2	2
Conductor twisting	No	No
Outer jacket	Flexible PVC	Flexible PVC
Outer jacket colour	Black with red molded line White with black molded line Grey with white molded line	Black with red molded line White with black molded line Grey with white molded line
Outer jacket dimensions	2,6 x 5,2 mm	3 x 6 mm
Lead resistance - 100 meter	2,3 Ohm	1,2 Ohm
Cable crosstalk - 100 meter	Min 74 dB	Min 74 dB
Cap. Lead to lead - meter @ 1 kHz	76 pF	95 pF

Cable model	RZ25	RZ40
Type of cable	Speaker cable	Speaker cable
Inner conductor	BC 30 x 7 x 0,12 mm	BC 50 x 7 x 0,12 mm
Inner conductor section	2,5 mm ²	4 mm ²
Number of conductors	2	2
Conductor twisting	No	No
Outer jacket	Flexible PVC	Flexible PVC
Outer jacket colour	Black with red molded line White with black molded line Grey with white molded line	Black with red molded line White with black molded line Grey with white molded line
Outer jacket dimensions	4 x 8 mm	5 x 10 mm
Lead resistance - 100 meter	0,9 Ohm	0,5 Ohm
Cable crosstalk - 100 meter	Min 74 dB	Min 74 dB
Cap. Lead to lead - meter @ 1 kHz	118 pF	128 pF



Available Lengths:
100 m plastic reel
500 m Wooden reel



RZ07G



RZ07W

MECHANICAL SPECIFICATIONS

Temperature range	fixed installation	-40° C till +80° C
	flexible installation	-25° C till +70° C
Bending radius	fixed installation	8 x outer diameter
	flexible installation	10 x outer diameter

