



## SC21H-N

HighSecLabs 2-Port 4K30 UHD HDMI KVM  
Combiner

| HDMI | C-KVM



SC21H-N is a 2-port 4K30 UHD HDMI KVM combiner. It enables users to share peripherals – keyboard, video, mouse, audio and USB – between two different networks/computers. Advanced multiviewer and scaling capabilities enable increased productivity in environments that require viewing and interacting with many computers simultaneously

### FEATURES

**Increase Work Efficiency** - View content on one large screen instead of multiple small screens while saving desk area in space restricted environments

**Freeze Audio** - Assign the audio port to a specific computer while switching the keyboard, video and mouse between other computers. Useful for scenarios where a user has to listen to audio originating from one computer while working on another computer

**Copy & Paste** - Transfer text and files between all the computers that are connected to the KVM switch (no network connection is needed between parties). Use standard copy and paste keyboard key combinations (CTRL+C / CTRL+V) or context-menu commands

**Native Touch Screen Support** - Interact with all connected computers using touch screen gestures, with no need for additional drivers or software. Compatible with standard Microsoft™ Digitizer driver-based touch screens without internal hubs



# KRAMER

## TECHNICAL SPECIFICATIONS

---

Console Ports	1 HDMI 1.4 connector;2 USB-A connectors for keyboard and mouse;1 3.5mm mini jack for unbalanced stereo audio;1 3.5mm mini jack for microphone;1 3.5mm mini jack connector for control (RDC)
Computer Ports	2 HDMI 1.4 connectors;2 USB-B connectors for keyboard and mouse;2 3.5mm mini jacks for unbalanced stereo audio;2 3.5 mini jacks for microphone
Max Output Resolution	1900x1200
Max Input Resolution	1920x1200
Power Consumption	12V DC, 1.5A
AC Input	100V to 240V AC
Power Type	External
Operating Temperature	0° to +40°C (32° to 104°F)
Storage Temperature	-20° to +60°C (-4° to 140°F)
Humidity	0% to 80%, RH non-condensing
Supported OS	Windows, Linux, Mac
Product Certification	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada
Product Life-cycle	10 years