



SK41HU-N

HighSecLabs 4-Port 4K30 UHD HDMI KVM
Switch with sUSB

| HDMI | C-KVM



SK41HU-N is a 4-port 4K30 UHD HDMI KVM switch. It enables users to share peripherals – keyboard, video, mouse, audio and USB – between four different networks/computers. It also enables assigning a USB port to a specific computer while switching other peripherals, such as when a USB smart card reader must remain mapped to a certain computer

FEATURES

4K30 UHD Resolution - Supports resolutions up to 3840×2160

Copy & Paste - Transfer text and files between all the computers that are connected to the KVM switch (no network connection is needed between parties). Use standard copy and paste keyboard key combinations (CTRL+C / CTRL+V) or context-menu commands

Freeze USB - Assign the USB port to a specific computer while switching the keyboard, video, mouse and audio peripherals between other computers. Useful when a USB device such as a disk-on-key must remain mapped to a certain computer, while the user is working on another computer

Freeze Audio - Assign the audio port to a specific computer while switching the keyboard, video, mouse and USB peripherals between other computers. Useful for scenarios where a user has to listen to audio originating from one computer while working on another computer

Super Speed USB 3.0 Ports - Transfer data and files between peripherals and computers USB 3.0 Super Speed rates through the KVM switch USB 3.0 ports

Express USB Charging - Rapidly charge USB devices connected to the high-power USB ports



KRAMER

TECHNICAL SPECIFICATIONS

Console Ports	1 HDMI 1.4 connector;2 USB-A connectors for keyboard and mouse;4 USB-A 3.0 connectors for USB devices;1 3.5mm mini jack for unbalanced stereo audio;1 3.5mm mini jack for microphone;1 RJ-45 connector for control (RDC)
Computer Ports	4 HDMI 1.4 connectors;4 USB-B connectors for keyboard and mouse;4 USB-B 3.0 connectors for USB devices;4 3.5mm mini jacks for unbalanced stereo audio;4 3.5mm mini jacks for microphone
Max Resolution	4K30 UHD (3840X2160)
Power Consumption	12V DC, 1.5A
AC Input	100 to 240V AC
Power Type	External
Operation Temperature	32° to 104°F (0° to +40°C)
Storage Temperature	-4° to 140°F (-20° to +60°C)
Humidity	10% to 80%, RH non-condensing
Supported OS	Windows, Linux, Mac
Product Certification	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada
Product Life-cycle	10 years