

SM40NU-N

HighSecLabs 4Port KM Switch

| C-KVM



SM40NUN is a 4port KM switch. It enables users to share peripherals keyboard, mouse, audio and USB between four different networks/computers. It also enables assigning a USB port to a specific computer while switching other peripherals, such as when a USB smart card reader must remain mapped to a certain computer

FEATURES

Multi Display Support - Enables switching keyboard and mouse control between computers, when each computer is connected to up to 4 displays (either extended or duplicated)

Copy & Paste - Transfer text and files between all the computers that are connected to the KVM switch (no network connection is needed between parties). Use standard copy and paste keyboard key combinations (CTRL+C / CTRL+V) or context-menu commands

Super Speed USB 3.0 Ports - Transfer data and files between peripherals and computers USB 3.0 Super Speed rates through the KVM switch USB 3.0 ports

Express USB Charging - Rapidly charge USB devices connected to the highpower USB ports



TECHNICAL SPECIFICATIONS

Console Ports 2 USBA connectors for keyboard and mouse;4 USBA 3.0 connectors for USB

devices;1 3.5mm mini jack for unbalanced stereo audio;1 3.5mm mini jack for

microphone;1 RJ45 connector for control (RDC)

Computer Ports 4 USBB connectors for keyboard and mouse;4 USBB 3.0 connectors for USB

devices;4 3.5mm mini jacks for unbalanced stereo audio;4 3.5mm mini jack for

microphone

Power Consumption 12V DC, 1.5A

AC Input 100V to 240V AC

Power Type External

Operating Temperature

0° to +40°C (32° to 104°F)

Storage Temperature 20° to +60°C (4° to 140°F)

Humidity 0% to 80%, RH noncondensing

Supported OS Windows, Linux, Mac

Product Certification CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

Product Life-cycle 10 years