



KRAMER

SX22H-N

HighSecLabs 2x2 4K30 UHD HDMI
Mini-Matrix KVM Switch

| HDMI | C-KVM



SX22H-N is a 2x2 4K30 UHD HDMI mini-matrix KVM switch. It enables viewing and controlling two computers simultaneously while sharing peripherals – keyboard, video, mouse, and audio devices

FEATURES

Small Form Factor - Occupies minimum desktop space

4K30 UHD Resolution - Supports resolutions up to 3840×2160 @30Hz

Independently Switch Peripherals Between Computers - Use the front-panel push buttons to independently switch the video, audio, USB, and keyboard-mouse ports between the different computers. Enables, for example: Keeping a USB flash drive mapped to a certain computer, while switching the other peripherals to another computer; or listening to audio originating from one computer while working on another computer

Smooth Switching Between Computers (Virtual Display Technology) - Automatically switch all peripheral control from one computer to another by dragging the cursor between each computer's display border

Work Simultaneously on Two Computers - Present the display of any connected computer on both mini-matrix displays at the same time or extend the displays to additional 3rd and 4th external displays

Copy & Paste - Transfer text and files between all the computers that are connected to the KVM switch (no network connection is needed between parties). Use standard copy and paste keyboard key combinations (CTRL+C / CTRL+V) or context-menu commands



KRAMER

TECHNICAL SPECIFICATIONS

Console Ports	2 HDMI 1.4 connectors;2 USB-A connectors for keyboard and mouse;1 3.5mm mini jack for unbalanced stereo audio;1 3.5mm mini jack for microphone;1 3.5mm mini jack connector for control (RDC)
Computer Ports	2 HDMI 1.4 connectors;2 USB-B connectors for keyboard and mouse;2 3.5mm mini jacks for unbalanced stereo audio;2 3.5mm mini jacks for microphone
MAX RESOLUTION:	4K30 UHD (3840X2160 @30Hz)
Power Consumption	12V DC, 1.5A
AC Input	100 to 240V AC
Power Type	External
Operating Temperature	32° to 104°F (0° to 40°C)
Storage Temperature	-4° to 140°F (-20° to 60°C)
Humidity	0-80% RH, non-condensing
Supported OS	Windows, Linux, Mac
Product Certification	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada
Product Life-cycle	10 years