



KRAMER

TP-573

HDMI HDCP 2.2 Transmitter with RS-232 &
IR over PoC Long-Reach DGKat

| HDMI | HDCP Compliant | DGKat | Kramer Core
| HDCP 2.2 Compatible



The TP-573 is a DGKat™ twisted pair transmitter for HDMI, bidirectional RS-232 and infrared signals. The TP-573 converts the input signals to a twisted pair signal and the TP-574 converts it back to HDMI, RS-232 and infrared signals

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel)

HDTV Compatible

HDCP Compliant

DGKat™ Signal Integration - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables

HDMI Support - x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD

3D Pass-Through

EDID PassThru - Passes EDID signals between the source and display

Bidirectional RS-232 & IR Interface - 38400 max baud rate

System Range - Up to 90m (295ft) at 1080i @60hz or up to 70m (230ft) at 1080p @ 60hz when using Kramer DGKat cables. Note: Transmission range depends on the signal resolution, graphics card and display used. If using third-party shielded CAT cables, both ends of the shield must be soldered to the connectors for the products to function properly

Power Connect System™ - A single connection to the transmitter powers both units

Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI connector, 1 bidirectional IR port on a 3.5mm mini jack, 1 bidirectional RS-232 port on a 9-pin D-sub connector
OUTPUTS:	1 CAT 5 OUT on an RJ-45 connector
BANDWIDTH:	4.95Gbps (1.65Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
POWER CONSUMPTION:	12V DC, 510mA
INCLUDED ACCESSORIES:	12V DC power supply
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx

