



## TP-580R

4K60 4:2:0 HDMI HDCP 2.2 Receiver with RS-232 & IR over Long-Reach HDBaseT



The TP-580R is a 4K UHD, twisted pair receiver for HDMI, bidirectional RS-232 and IR signals. It supports resolutions up to 4K@60 UHD (4:2:0). The TP-580T converts HDMI, RS-232, and IR signals into a twisted pair signal that it transmits to a TP-580R receiver. The TP-580R converts the twisted pair signal back into HDMI, bidirectional RS-232 and IR signals.

## FEATURES

- Resolution Support. - Up to 4K@60 UHD (4:2:0).
- Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliance.
- HDBaseT™ Technology.
- HDMI Support - Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD, CEC.
- 3D Pass-Through.
- EDID PassThru - Passes EDID signals between the source and display.
- Bidirectional RS-232 & IR Interface. - Commands and data can flow in both directions via the RS-232 interface, allowing status requests and remote control of the destination unit.
- System Range - 70m (230ft) @1080p, 40m (130ft) @4K.
- Cable - For optimum range and performance using HDBaseT™, use Kramer's BC-HDKat6a cable. Note that the transmission range depends on the signal resolution, source and display used. The distance using non-Kramer CAT 6 cable may not reach these ranges.
- Indicators - Status LEDs for input, output, link and power.
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T universal rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	1 twisted pair RJ-45 connector.
OUTPUTS:	1 HDMI connector.
PORTS:	1 IR on a 3.5mm mini jack, 1 RS-232 on a 9-pin D-sub connector.
BANDWIDTH:	10.2Gbps (3.4Gbps per graphic channel).
RS-232 BAUD RATE:	115200.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
POWER CONSUMPTION:	12V DC, 430mA.
OPERATING TEMPERATURE:	0° to 40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	12cm x 7.15cm x 2.44cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.2kg (0.44lbs).
INCLUDED ACCESSORIES:	2 power supplies.
OPTIONS:	RK-T2B 19" rack mount, Kramer external IR sensor (P/N: 95-0104050), Kramer IR emitter cable (P/N: C-A35/IRE-10), Kramer BC-HDKat6a cable.

