

## TR-1

Video Isolation Transformer



The TR-1 is a high-resolution isolation transformer for composite video signals. It completely isolates devices to eliminate video hum, ground loops, and DC offsets that can degrade picture quality

## **FEATURES**

Bandwidth - 5.8MHz (-3dB)

Passive Device - No power required



## TECHNICAL SPECIFICATIONS

INPUT: 1 composite video,  $1\mbox{Vpp}/75\Omega$  on a BNC connector

OUTPUT: 1 composite video,  $1Vpp/75\Omega$  on a BNC connector

**INSERTION LOSS:** 0.8dB

MAX. OUTPUT

LEVEL:

 $4Vpp/75\Omega$ 

BANDWIDTH (-3dB): 5.8MHz

DIFF. GAIN:

0.05%

DIFF. PHASE:

0.05Deg

K-FACTOR:

1.2%

S/N RATIO:

73.4dB

TILT:

0.1%

NON-LINEARITY:

0.1%

COUPLING:

Transformer

**POWER** 

None, passive device

CONSUMPTION:

**INCLUDED** 

ACCESSORIES:

Mounting brackets

**PRODUCT** DIMENSION:

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx **SHIPPING** 

23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H

 $12.12cm \times 7.23cm \times 3.07cm (4.77" \times 2.85" \times 1.21")$  W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.4kg (1.0lbs) approx

