



# TT-SD209-FS-DS

55" Digital Signage Info-Stele, Indoor, SPERRGUT

Hohe Aufmerksamkeit für die Botschaft: Der digitale Infopoint, Modell Tim Touch von Billboard Media ist mit seinem modernen Design ein absoluter Hin-gucker.

Zu verwenden für z.B. digitale Werbung, Ihren Event-kalender und Ihre digitale Speisekarte.

Durch die Multitouchfunktion eignet sich der digitale Aufsteller bestens als Wegleitsystem und digitale Touristeninformation oder digitale Amtstafel. Das 55 Zoll große Display ist für den Betrieb 27/7 geeignet.

Die Aufmerksamkeit von Digital Signage Produkten erhöht sich gegenüber von analogen Plakaten um 70%.





Physical Features				
Touch Screen	Touch screen type	Capacitive Touch (G+G)		
	Touch condition	Finger, touch pen		
	Touch points	10 points		
	Response time	≤ 10m-sec		
	Sensor quantity	4K		
	Touch accuracy	±1mm		
	Supported OS	Windows, Linux, Android		
	Light transmittance	≥89%		
Panel	Item	Specifications	Unit	
	Panel size	55	inch	
	Panel backlight	TFT-LCD	/	
	Active display area	1209.6*680.4	mm	
	Number of pixel	1080x1920	pixel	
	Luminance of white	350 (Typ.)	nits	
	Contrast ratio	2000:1	/	
	Viewing angle	178/178 (wide)	degree	
	Aspect ratio	16:9	/	
	Response time	6	m-sec	
	Life time	60,000	hours	
	Monitor Control Board Specifications	Chipset	NT68676(UFG)	
OSD Language		Simplified Chinese, Traditional Chinese, English, French, German, Italian, Spanish, Portuguese, Japanese, Korean (Optional) MP3, WMA		
Panel Support		Max Resolution:1920x1080P		
Video input		PC Audio	Earphone Input	0.2 ~ 2.0 Vrms
Frequency Response		100Hz~15KHz @±3dB (1KHz, 0dB reference signal)		
Max Output Power		2 x 1W(8Ω) THD+N<10%@1KHz (Power Supply: 12V, Audio Input: 0.5Vrms)		
I/O		HDMI x 1, DVI x 1, PC-RGB x1, PC audio-in x1, 3.5 jack plu		
Tip: In consideration of public safety, our standard unit has a door&lock for all the sockets. Please contact us, if no needed.				
English (default) and multi language				
Appearance		Colors	Silver frame and black body color	
	Surface treatment	Powder coated		
	Shell material	aluminium frame, tempered glass face & cold-rolled sheet body		
	Screen position	Portrait (default) or Landscape		
	Wheels	Optional		
	Installation	Free-standing		
Other	Loudspeaker	Yes, 8 Ohm/ 5 watt *2 pcs		
	Power input	AC 100 ~ 240V, 50/60 Hz		
	IP code	IP20		
	Working temperature	0 to 40°		
	Storage temperature	-15°C to 50°C		
	Working temperature	20% ~ 80%		
	Storage temperature	10% ~ 90%		
	Unite Package	PE film + Foam corner protector + Carton		
	Export Package	Export wooden box or wooden pallet		
	Accessories	8G SD card*1, remote control*1, Floor stand bracket&screws *1, key*1		

