

Highlights:

- Powerful sound experience
- High sound pressure levels with tight driver response
- Modern & elegant design
- Impact resistant
- DuraCoat™ texture paintwork
- Horizontal and vertical mounting
- Inclined Speakon connectors
- 70V/100V transformer option available
- Optional clever U-bracket

Product information:

The most compact VEXO100 series models pack a surprising punch. For its compact size, the VEXO106 plays in a different league, offering unrivaled brilliance and a high power output. The VEXO1xx series are compact high performance 2-way loudspeakers and come in 5 different (active or passive) models. The low-frequency transducer, which is made out of high-quality materials, is combined with a 1" (VEXO106), 1.4" (VEXO108) or 1.7" (VEXO110, VEXO112 & VEXO115) voice coil compression driver, enabling high sound pressure levels and a tight driver response.

Thanks to the unique driver composition, the VEXO106 delivers a clear and natural sound with a continuous power of 125 Watts and a maximum power of 500 Watt. The frequency response ($\pm 3\text{dB}$) starts from 80Hz up to 25 kHz and the sensitivity (1W/1m) reaches 92dB while a maximum continuous sound pressure level from 113dB can be achieved.

Using an optional 70V/100V line transformer enables the VEXO series to be used in 70V or 100V systems. By removing the backplate and replacing it with a 70V/100V backplate on which the module is integrated, the high-performance loudspeaker is able to apply in a 70V/100V system.

The construction of the cabinets is made of 15 mm plywood with a polyurethane coating, making them resistant to any impact. The front side of the cabinet is finished with a powder-coated steel grill with acoustical foam. The VEXO106, unlike its bigger brothers, does not come with a recessed carry handle on the rear side. However, positioning and suspension of the speaker are easily achieved by using the M8 rigging points. Two speaker connectors provide reliable connections with easy link-through to cabinets.

The optional Clever U bracket allows mounting the high power 2-way cabinet both horizontally and vertically. This optional bracket even allows mounting the VEXO series to the ceiling which gives the opportunity to install the loudspeaker cleanly in any environment.



Impedance:

Ω 8 Ohm

Applications:

- Bars & Restaurants
- Education
- Clubs
- Sporting facilities
- Events
- Concert venues

System specifications:

Speaker type		2-way
Peak power handling		500 W
Program power handling		250 W
Continuous power (AES)		125 W
Impedance		8 Ω
Sensitivity (1W/1m)		92 dB
Max SPL (Continuous)		113 dB
Frequency	Response (\pm 3 dB)	80 Hz - 25 kHz
	Range (-10 dB)	63 Hz - 20 kHz
Crossover	Type	Passive built-in
Dispersion	Horizontal	110°
	Vertical	90°
Drivers	HF	1" Compression driver
	LF	6.5"
Connectors		2 x Speakon compatible (Linkthrough)

Product Features:

Dimensions		196 x 355 x 205 mm (W x H x D)
Weight		6.33 kg
Construction		15 mm Multiply Plywood with Polyurea coating
Front finish		Powder coated steel grill with acoustical foam
Mounting & handling	Rigging points	1 x M8 (bottom)
		1 x M8 (top)
		1 x M10 - drop safety (rear)
Accessories	Optional	70V/100V transformer module
		MBK106V - Mounting bracket for VEXO106
		MBK500 - Two-way revolving mounting bracket
Colours		Black & White

Variants:

- VEXO106/B - Black version
- VEXO106/W - White version

Shipping & Ordering:

Shipping weight & volume	15.2 kg - 0.06 Cbm (pair)
Packaging	Cardboard box (pair)