



KRAMER

VGAA-IN4-F32

4-Channel VGA with Analog Audio Input
Card

| Kramer Core



VGAA-IN4-F32 is a four-channel VGA with analog audio input card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. VGAA-IN4-F32 inputs four VGA with analog audio signals into the chassis. Audio is accessed by connecting the supplied Kramer VGA with audio cables to each VGA port

FEATURES

- Max. Bandwidth - 450MHz
- HDTV Compatible
- Analog Audio Over Breakaway Connector



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS	4 VGA on 15-pin HD connectors, 4 unbalanced analog audio on 3.5mm mini jack connectors (accessible via C GF/GMAF-30 cables)
BANDWIDTH:	450MHz
MAXIMUM RANGE:	10m (32ft)
Power Consumption	20W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
INCLUDED ACCESSORIES:	4 C-GF/GMAF-30 cables
PRODUCT DIMENSION:	22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H
PRODUCT WEIGHT:	0.3kg (0.7lbs) approx
SHIPPING DIMENSION:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	0.5kg (1.2lbs) approx