

VGA-OUT2-F16

2-Channel VGA Output Card

| Kramer Core



VGA-OUT2-F16 is a two-channel VGA output card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGA-OUT2-F16 outputs two VGA signals from the chassis

FEATURES

Max bandwidth - 450MHz Auto or User-Defined Resolution Detection & Phase Mode Adjustable Brightness & Contrast



TECHNICAL SPECIFICATIONS

PORTS:	2 VGA on 15-pin HD connectors
BANDWIDTH:	450MHz
MAXIMUM RANGE:	10m (32ft)
POWER CONSUMPTION:	4W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
PRODUCT DIMENSION:	19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79") W, D, H
PRODUCT WEIGHT:	0.2kg (0.3lbs) approx
SHIPPING DIMENSION:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
SHIPPING WEIGHT:	0.4kg (0.8lbs) approx