

## **VM-1021N**

1:20 Composite/SDI Video Distribution Amplifier



The VM-1021N is a high-performance distribution amplifier for composite or SD-SDI video signals. It provides controls to compensate for signal losses inherent in long cable runs

## **FEATURES**

High Bandwidth - 350MHz (-3dB)
Grouped Level (Gain) and EQ (Peaking) Controls
Looping Input
Selectable Input Signal Termination
DC Coupling



## **TECHNICAL SPECIFICATIONS**

INPUT: 1 composite video/single component with loop,  $1Vpp/75\Omega$  on a BNC connector with

termination switch

OUTPUTS: 20 composite/component video,  $1Vpp/75\Omega$  on BNC connectors

VIDEO BANDWIDTH 350MHz

(-3dB):

DIFF. GAIN: 0.1%

DIFF. PHASE: 0.07Deg

K-FACTOR: <0.05%

VIDEO S/N RATIO: 74dB

CONTROL: Level: -1.1dB to + 2.7dB; EQ.: 0 to 2.9dB @4.4MHz

NON-LINEARITY: 0.1%

COUPLING: DC

POWER 230V AC, 50/60Hz (115V USA), 6.7VA

CONSUMPTION:

OPERATING  $0^{\circ}$  to  $+40^{\circ}$ C (32° to  $104^{\circ}$ F)

TEMPERATURE:

STORAGE  $-40^{\circ}$  to  $+70^{\circ}$ C ( $-40^{\circ}$  to  $158^{\circ}$ F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

INCLUDED

ACCESSORIES:

Power cord

PRODUCT

19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H

DIMENSION:

PRODUCT WEIGHT: 1.6kg (3.6lbs) approx

SHIPPING DIMENSION:

55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

SHIPPING WEIGHT: 2.5kg (5.4lbs) approx

