

VM-10xl

1:10 Composite Video & Stereo Audio Distribution Amplifier



The VM-10xl is a broadcast quality 1:10 distribution amplifier for composite or SDI video signals with unbalanced stereo or balanced mono audio. It provides controls to compensate for signal losses inherent in long cable runs

FEATURES

High Bandwidth - 360MHz (-3dB) Audio Controls Level (Gain) and EQ (Peaking) Controls Looping Input Selectable Input Signal Termination Video AC/DC Coupling Selection Standard 19" Rack Mount Size - 1U



TECHNICAL SPECIFICATIONS

INPUTS:	1 composite video with loop, $1Vpp/75\Omega$ with termination switch on BNC connectors; 2 balanced stereo/mono audio with loop, $1Vpp/50k\Omega$ on RCA connectors
OUTPUTS:	10 composite video, 1Vpp/75 Ω on BNC connectors; 10 balanced stereo/mono audio, 1Vpp/50 Ω on RCA connectors
MAX. OUTPUT LEVEL:	Video: 1.6Vpp; Audio: 26.5Vpp
BANDWIDTH (-3dB):	Video: 360MHz, Audio: 100kHz
DIFF. GAIN:	0.07%
DIFF. PHASE:	0.05Deg
K-FACTOR:	<0.05%
S/N RATIO:	Video: 77dB, Audio: 87dB
CONTROLS:	Video level: (-1.2dB to +6dB), EQ. (0dB to +8.1dB); audio level: (0dB to +6dB); balanced/stereo selector switch and audio control enable switch
COUPLING:	Video: DC/AC; Audio: AC (input), DC (output)
AUDIO THD + NOISE: 0.023%	
AUDIO 2nd HARMONIC:	0.001%
POWER CONSUMPTION:	230V AC, 50/60Hz, (115V USA), 4.7VA
INCLUDED ACCESSORIES:	Power cord
PRODUCT DIMENSION:	19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H
PRODUCT WEIGHT:	1.7kg (3.7lbs) approx
SHIPPING DIMENSION:	0.00cm x 0.00cm x 0.00cm (0.00" x 0.00" x 0.00") W, D, H
SHIPPING WEIGHT:	2.5kg (5.6lbs) approx

