

VM-12HDCP

1:12 DVI (HDCP) Distribution Amplifier

| DVI | HDCP Compliant



The VM-12HDCP is an HDCP-compliant distribution amplifier for DVI-D signals with resolution up to 1080p or UXGA. It reclocks and equalizes the signal and distributes it to twelve identical outputs

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel) HDTV Compatible HDCP Compliant HDMI Support - HDMI Compressed Audio Channels Kramer Equalization & re-Klocking[™] Technology - Rebuilds the digital signal to travel longer distances EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for DVI source and display systems Active Input & Output LED Indicators Worldwide Power Supply - 100-240V AC



TECHNICAL SPECIFICATIONS

INPUT:	1 DVI-D on a DVI-I connector, 1.2Vpp; DDC signal 5Vpp (TTL)
OUTPUTS:	12 DVI-D on DVI-I connectors, 1.2Vpp; DDC signal 5Vpp (TTL)
BANDWIDTH:	4.95Gbps (1.65Gbps per graphic channel)
CONTROLS:	SELECT and READ buttons for selecting and storing EDID information
POWER CONSUMPTION:	100-240V AC, 50/60Hz, 11VA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	−40° to +70°C (−40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Power cord, rack "ears"
PRODUCT DIMENSION:	19" x 9.34 x 1U (43.6cm x 23.72cm x 4.36cm) W, D, H
PRODUCT WEIGHT:	2.1kg (4.6lbs) approx
SHIPPING DIMENSION:	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
SHIPPING WEIGHT:	3.0kg (6.5lbs) approx

