



KRAMER

VM-24HDCP

2x1:4 DVI (HDCP) selectable DA

| DVI



The VM-24HDCP is a high-performance distribution amplifier for DVI signals. The unit reclocks and equalizes one of two input signals and distributes it to four identical outputs

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

HDTV Compatible

HDCP Compliant

HDMI Support - HDMI Compressed Audio Channels

EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for DVI source and display systems

Control - Front panel & IR switching

Worldwide Power Supply - 100-240V AC

Standard 19" Rack Mount Size - 1U. Rack "ears" included



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---|
| INPUTS: | 2 DVI, 1.2Vpp on a DVI Molex 24-pin (F) connector; DDC signal 5Vpp (TTL) |
| OUTPUTS: | 4 DVI, 1.2Vpp on DVI Molex 24-pin (F) connectors; DDC signal 5Vpp (TTL) |
| MAX. DATA RATE: | 6.75Gbps (2.25Gbps per graphic channel) |
| CONTROLS: | EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS-232, IR |
| INDICATOR LEDs: | OUTPUT STATUS LEDs |
| POWER CONSUMPTION: | 100-240V AC, 50/60Hz 17VA |
| INCLUDED ACCESSORIES: | Power cord, rack "ears", null-modem adapter, Windows®-based control software, infrared remote control transmitter |
| PRODUCT DIMENSION: | 19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H |
| PRODUCT WEIGHT: | 1.5kg (3.3lbs) approx |
| SHIPPING DIMENSION: | 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H |
| SHIPPING WEIGHT: | 2.3kg (5.1lbs) approx |

