



KRAMER

VS-42HDCP

4x2 HDCP Compliant DVI Matrix Switcher

| Ethernet - RJ-45 | HDCP Compliant



The VS-42HDCP is a high-quality, HDCP compliant 4x2 HDMI (on DVI connectors) matrix switcher. It reclocks and equalizes the signals and can route any of the four DVI/HDMI (over DVI-D connector) inputs to any of the two DVI/HDMI outputs simultaneously

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

HDCP Compliant

HDMI Support - Deep Color, x.v.Color™, 3D Pass-Through

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

7.1 Multi-Channel Audio

Front Panel Control Lockout

Communication Support - Support for Kramer Protocol 2000 and Protocol 3000

Flexible Control Options - Front panel, IR (remote included), RS-232 (K-Router Plus™ Windows®-based software is included), Ethernet (Windows®-based Ethernet Configuration Manager & Virtual Serial Port Manager is included), remote extension cable transmitter (optional)

Worldwide Power Supply - 100-240V AC



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|--|
| INPUTS: | 4 DVI connectors |
| OUTPUTS: | 2 DVI connectors |
| BANDWIDTH: | Up to 6.75Gbps data rate (2.25Gbps per graphic channel) |
| COMPLIANCE WITH STANDARDS: | Supports DVI and HDCP |
| MAX RESOLUTION: | Up to UXGA; 1080p |
| POWER SOURCE: | 100-240V AC; 50/60Hz, 20VA |
| CONTROLS: | Front panel buttons, infrared remote control transmitter, RS-232, Ethernet |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power cord, IR transmitter, rack "ears" |
| OPTIONS: | External remote IR receiver cable |
| PRODUCT DIMENSION: | 19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H |
| PRODUCT WEIGHT: | 1.9kg (4.2lbs) approx |
| SHIPPING DIMENSION: | 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H |
| SHIPPING WEIGHT: | 2.7kg (6.0lbs) approx |

