

WX502 Wall Speaker

Features

- Powerful 2-way wall speaker
- True-to-nature sound reproduction
- Available in 3 different colours
- Vertical or horizontal mounting
- Mounting bracket is included
- Easy installation
- Aluminium grill
- Adjustable power tapping

Applications

- Wide variation of indoor applications
- Private houses
- Halls, pubs
- Restaurants
- Stores
- Warehouses



The AUDAC WX series speakers are powerful 2-way performance speakers for a wide variety of applications, ensuring true-to-nature, high-fidelity reproduction of music and speech.

They WX502 has a 5" low frequency loudspeaker and a 1" dome tweeter and is built in a synthetic enclosure, which makes the speaker suitable for all purposes. The speaker is suitable for standard home indoor installations to specialized indoor design appliances. Due to the construction, the speaker can be mounted vertically or horizontally, using the included wall bracket.

This loudspeaker is available in three colours: white, black and silver. It is standard delivered with a wall mounting bracket in the same colour as the speaker.

With a recessed adjuster screw at the rear the power can be set in 3 adjustable steps of impedance for 100V and 1 step for 8 Ohm standard low impedance applications.

- 40 Watt, 20 Watt, 10 Watt @ 100 V
- 50 Watt @ 8 Ohm

▶ Specifications

Speaker type	SYSTEM SPECIFICATIONS				
RMS power S0 Watt Impendance 8 Ohm Eline transformer taps 1	Speaker type		2-way		
Impendance	Max. power		100 Watt		
Line transformer taps	RMS power		50 Watt		
2 20 Watt / 500 Ohm 3 10 Watt / 1000 Ohm Sensitivity (1W/1m) 87 dB Sound pressure Max W / 1m @ 8 Ohm 104 dB Sound pressure Max W / 1m @ 100 V 102 dB Frequency response (± 3 dB) 70 Hz - 18 kHz Frequency range (-10 dB) 55 Hz - 20 kHz Cross-over type Passive built-in Cross-over frequency 2.5 kHz Horizontal dispersion 110° Vertical dispersion 110° IP rating (Ingress Protection) 40 PRODUCT FEATURES Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	•		8 Ohm		
3	Line transformer taps	1	40 Watt / 250 Ohm		
Sensitivity (1W/1m)		2	20 Watt / 500 Ohm		
Sound pressure Max W / 1m @ 8 Ohm Sound pressure Max W / 1m @ 100 V Frequency response (± 3 dB) Frequency range (-10 dB) Cross-over type Passive built-in Cross-over frequency Province dispersion Frequency Frequency Province dispersion Provertical dispersion Provertical dispersion Provertical dispersion Frequency Provertical dispersion Provertical dispersion Provertical dispersion Provertical dispersion Frequency Fre		3	10 Watt / 1000 Ohm		
Sound pressure Max W / 1m @ 100 V 102 dB			87 dB		
Frequency response (± 3 dB) 70 Hz - 18 kHz Frequency range (-10 dB) 55 Hz - 20 kHz Cross-over type Passive built-in Cross-over frequency 2.5 kHz Horizontal dispersion 110° Vertical dispersion 110° IP rating (Ingress Protection) 40 PRODUCT FEATURES Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Cardboard box	Sound pressure Max W / 1m @ 8 Ohm		104 dB		
Frequency range (-10 dB) 55 Hz - 20 kHz Cross-over type Passive built-in Cross-over frequency 2.5 kHz Horizontal dispersion 110° Vertical dispersion 110° IP rating (Ingress Protection) 40 PRODUCT FEATURES Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Cardboard box	Sound pressure Max W / 1m @ 100 V		102 dB		
Cross-over type Passive built-in Cross-over frequency 2.5 kHz Horizontal dispersion 110° Vertical dispersion 110° IP rating (Ingress Protection) 40 PRODUCT FEATURES Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Cardboard box			70 Hz - 18 kHz		
Cross-over frequency 2.5 kHz Horizontal dispersion 110° Vertical dispersion 110° IP rating (Ingress Protection) 40 PRODUCT FEATURES Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	Frequency range (-10 dB)		55 Hz - 20 kHz		
Horizontal dispersion	Cross-over type		Passive built-in		
Vertical dispersion 110° IP rating (Ingress Protection) 40 PRODUCT FEATURES Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	Cross-over frequency		2.5 kHz		
IP rating (Ingress Protection) 40	Horizontal dispersion		110°		
PRODUCT FEATURES Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box			110°		
Dimensions (Width x Height x Depth) 212 x 147 x 136 mm Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box			40		
Weight net 2.54 Kg Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	PRODUCT FEATURES				
Drivers HF 1" LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	Dimensions (Width x Height x Depth)		212 x 147 x 136 mm		
LF 5" Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	Weight net				
Construction ABS housing Grill type Aluminium grill Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	Drivers	HF			
Mounting & handling Mounting bracket		LF	5"		
Mounting & handling Mounting bracket Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box	Construction		ů		
Available colours White (RAL 9010) WX502/W Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box			0		
Black (RAL 9005) WX502/B Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box					
Silver (RAL 9006) WX502/S SHIPPING & ORDERING Packaging Cardboard box			White (RAL 9010)	WX502/W	
SHIPPING & ORDERING Packaging Cardboard box			Black (RAL 9005)	WX502/B	
Packaging Cardboard box			Silver (RAL 9006)	WX502/S	
Shipping weight & volume 5 8 Kg - 0 0185 Cbm	0 0				
11 0 0	Shipping weight & volume		5.8 Kg - 0.0185 Cbm		
Accessory included Mounting bracket	Accessory included		Mounting bracket		