

MAXHUB XBoard V7 Series

For Microsoft Teams Room

Model: V555T

Experience the ultimate in video conferencing and collaboration with the MAXHUB XBoard V7 series. Powered by a Windows PC module, this all-in-one design device seamlessly integrates an AI camera system, cutting-edge audio processing, interactive whiteboarding, and an intuitive meeting launcher, all housed within a single comprehensive collaboration display. This powerful combination enhances the dynamism of meetings and introduces a flexible and creative interaction to your organization.



Professional 4K Display

High color accuracy, $\Delta E \leq 1.5$
Wide color gamut, NTSC 90%
Non-glare technology, 25% haze



Seamless Collaboration

Built-in touch display and Microsoft
whiteboard for real-time
collaboration



Triple-Camera System

Equipped with one wide-view lens
and two tele-view lens to provide
clear view for all room participants



AI-Powered Video Technology

Auto framing
Speaker tracking
Multi-speaker tracking
Intelligent focus



Premium Audio

Built-in 16-beamforming
microphone array,
Built-in stereo speakers
AI-powered noise reduction
Full-duplex communication



Flexible Content Share

Wired 4K content share via HDMI In
Wireless content share via wireless
dongle or MAXHUB Share application



BYOD Mode

Plug-and-play, an accessible way
to switch between Teams Rooms
mode and BYOD mode



Peak Performance

Unleash the power with MT71 series
PC module. 12th Gen Intel Processor
with Windows system, stably smooth

Display	
Model	V555T
Screen Size (Inch)	55
Aspect Ratio	16:9
Panel	ADS
Backlight	DLED
Brightness (Typ.)	350 nits
Glass	Zero parallax 3 mm thickness 9H Tempered
Surface Technology	25% haze Non-glare technology
Resolution	3840 × 2160
Refresh Rate	60 Hz
Contrast Ratio	1200:1 (typ.)
Viewing Angle (H × V)	178° / 178°
Color Gamut	90% NTSC
Display Orientation	Landscape
Response Time	8 ms
Life Time	> 50,000 hours
Operation Hours (Hours / Day)	16 / 7
Display Color	1.07 B (10 bit)
Color Accuracy	Delta E ≤ 1.5
Sensor	Ambient light sensor Motion Sensor
Pixel Pitch	0.315 (H) × 0.315 (V) mm / 0.0124 (H) × 0.0124 (V) inch
Display Area	1209.6 (H) × 680.4 (V) mm / 47.62 (H) × 26.79 (V) inch

Power	
Power Supply	100-240V ~ 50/60 Hz
Standby Power	≤ 0.5 W
Power Consumption (Typ.)	101 W
Power Consumption (Max.)	320 W

Touch System	
Touch Technology	Intelligent Touchscreen Technology (Infrared recognition)
Touch Point	50 points touch
Object Recognition Range	≥ 1.5 mm / 0.06 inch
Accuracy	± 0.5 mm / 0.02 inch
Response Time	≤ 2.5 ms
Writing Height	≤ 1 mm / 0.04 inch

Connectivity	
I/O Ports (Interactive Display)	
HDMI In (2.0) × 2	To connect an external source (disabled as default, and can be enabled on MAXHUB Align app.)
USB-A 2.0 × 1	To pair with wireless dongle-WT13M/WT13S To connect keyboards or mouse, etc.
Touch (USB-B 2.0) × 1	To connect a personal laptop to access to XBoard's cameraµphone and get touch back (disabled as default, and can be enabled on MAXHUB Align app.)
Audio In × 1	To connect an external audio source to make XBoard a speaker
Audio Out × 1	3.5 mm mini-jack, to connect an external speaker system
RS232 × 1	9 pin
Mic In (RJ45) × 1	To connect up to a maximum of three UC BM45 as expansion speakerphones
Wireless Access Point	Yes (for wireless presentation)

Camera	
Wide Camera	50MP × 1 DFOV 99°, HFOV 86°
Telephoto Camera	50MP × 2 DFOV 68° (combined), HFOV 63° (combined)
Zoom	5x hybrid zoom
Privacy Shutter	Yes
AI Features	Auto Framing Speaker Tracking Multiple-Speaker Tracking Intelligent Focus

Audio	
Sound Channel	2.1
Speaker Power	2×10W + 20W

Microphone	
Quantity	16-mic array
Pick-up Angle	180°
Pick-up Range	Best distance – 8 m / 26.2 ft Maximum distance – 15 m / 49.2 ft
Feature	Intelligent audio fence AI spatial sound AEC (Auto echo cancellation) ANC (AI noise cancellation) AGC (Auto gain control)

Built-in PC Module		Physical Specification	
CPU	12th gen Intel Core i5 – 1240p	Product Dimension (W × H × D)	1269.5 × 800 × 104.4 mm / 49.98 × 31.5 × 4.11 inch
GPU	Intel® Iris® Xe Graphics eligible	Shipping Dimension (W × H × D)	1428 × 868 × 220 mm / 56.22 × 34.17 × 8.66 inch
Memory	16GB DDR4 (8GB ×2)	Thickness of Machine and Wall Mount	130 mm / 5.12 inch
Storage	256GB SSD (M.2)	Wall-hanging Screw Spec	M8 × 25 mm
Operating System	Windows 11 IOT	VESA	400 × 200 mm / 15.75 × 7.87 inch
TPM 2.0	Yes	Net Weight	26.5 kg / 58.42 lbs
Input & Output	USB-A (3.0) ×3	Gross Weight	37 kg / 81.57 lbs
	HDMI In (2.0) ×1 (For content share in Teams rooms mode, up to 4K resolution on local room display)	Environmental Condition	
	HDMI Out × 2 (Without actual function currently, hardware reserved for possible future use)	Operating Temperature	0°C~40°C
	RJ45 × 1 (Ethernet)	Storage Temperature	-20°C~60°C
	RJ45 × 1 (For optional touch console - TCP30T (avaible in early Q3 2025)	Operating Humidity	10%~90% RH
Wi-Fi	Wi-Fi 6	Storage Humidity	10%~90% RH
Bluetooth	Bluetooth 5.1	Altitude	Below 5000 meters

Accessory (Included in the Package)		Certification	
Wireless Module	AP	Safety	IEC 62368-1
HDMI Cable (3 m / 9.8 ft)	× 1	EMC	Class B
Power Cord	× 1	Warranty	
Passive Stylus	× 2	3-Year warranty	
Wall Mounts Kits	× 1		

Accessory (Optional)			
Mobile Stand ST33M / ST23G	Expansion Speakerphone UC BM45	Wireless Share Dongle WT13M / WT13S	Touch Console TCP30T (Avaible in Q2 2025)
			

Statement

Please note that the size and weight may vary by configuration and manufacturing process. For accurate product specifications, please refer to the actual product. Product images are for reference only and may di er slightly from the actual product in appearance, color, size, etc. The description, illustrations, etc. in this document may be subject to change in accordance with the latest product specification and performance. Should any changes be necessary, the document may be updated without written notice.



MAXHUB

Where Inspiration Moves Ahead.