

BrightSign®

BRIGHTSIGN XD5

PROFESSIONAL 4K PLAYERS FOR ENTERPRISE+ EXPERIENCES

BrightSign XD5 has been redesigned to power state of the art digital signage experiences featuring PoE, a thinner design and simplified Wi-Fi & SSD install. Its updated architecture delivers enhanced video and motion graphics at faster frame rates in 4K landscape or portrait orientations. Reengineered memory management makes HTML & JavaScript content faster and more responsive in presentations. BrightSign XD5 is manufactured along a stable supply chain allowing you to create inspiring digital signage experiences now and into the future.



FEATURES

Enterprise+ HTML Performance

- Optimized motion graphics performance
- Smooth animations & tickers with 60fps frame rates
- Highly responsive & fluid content interactions

Enhanced 4K Video Engine

- Hardware accelerated 4K rotation
- 4K60p video
- 4K images & graphic

Perfected Industrial Design

- Power over Ethernet (PoE+)
- Thinner footprint
- Simplified Wi-Fi and SSD installation
- Patented aluminum enclosure to dissipate heat

BrightSign OS

- Purpose-built for connected digital signage
- Delivers high reliability & security
- Unlocks features for full signage potential
- Guaranteed updates & longevity

XD235

Standard I/O Model



XD1035

Expanded I/O Model



BrightSign®

SPECIFICATIONS

MODEL	XD235 Standard I/O	XD1035 Expanded I/O
VIDEO & HTML ENGINES		
Native 4K@60p video	X	X
Hardware accelerated 4K rotation	X	X
Dynamic Mosaic Mode	X	X
4K image and motion graphic support	X	X
Dual video decoding	X	X
HDR10 and HLG	X	X
HTML5 performance level	Enterprise+	
Dynamic memory allocation	X	X
MEDIA FORMATS		
Video codecs for 4K content: H.265/H.264	X	X
Video Containers for 4K H.265 content: .ts, .mov, .mp4, .mkv	X	X
Video Codecs for Full HD: H.265, H.264(MPEG-4, Part 10), MPEG-2	X	X
Video Containers for Full HD content: .ts, .mpg, .vob, .mov, .mp4, .m2ts	X	X
Images: BMP, JPEG, PNG	X	X
Audio: MP2, MP3, AAC and WAV (AC3 is passed through)	X	X
HTML5: Chromium-based, Open GL ES	X	X
HARDWARE INTERFACES		
HDMI™ Output 2.0a	1	1
USB Type C port: supports high-speed host mode & provides 5V/1A power to peripheral devices		1
USB Type A port: provides 5V/1A power to peripheral devices		1
12-pin Phoenix GPIO port with 8 bi-directional GPIOs	X	X
3.5mm RS-232 Serial Port		X
3.5mm IR In/Out	X	X

MODEL	XD235 Standard I/O	XD1035 Expanded I/O
3.5mm Audio Out (analog & SPDIF digital)	X	X
Gigabit Ethernet with PoE+ (Power over Ethernet)	X	X
External micro SD Slot for primary storage	X	X
M.2 PCIe for optional NVMe SSD storage	X	X
E Key M.2 for optional dual antenna Wi-Fi/Bluetooth module	X	X
Status LEDs	4	4
Reset and Service Buttons	X	X
Real Time Clock	X	X
Locking Power Connector	X	X
ACCESSORIES		
USB Button Pads	X	X
WD-105 Dual Antenna Wireless/Bluetooth Module	X	X
MicroSD Class 10 Cards (various capacities)	X	X
NVME SSD	X	X
MISCELLANEOUS		
12V / 3A Power Supply	X	X
Perfected Industrial Design - Simplified Wi-Fi & SSD installation & Patented aluminum enclosure dissipates heat		X
Dimensions (W x H x D)	205 x 19.2 x 185.9 mm 8.07 x 0.756 x 7.32 in	
Weight	Coming Soon	
Power	12V / 3A (30 Watts)	
Multi-Country Power & Regulatory Approvals	X	X
Built-in Wall Mounting Brackets	X	X
1 year warranty, parts and labor*	X	X

*2 year warranty, parts and labor, for units shipped from an EU or UK distribution center and to an EU or UK address.

Copyright © 2022 by BrightSign, LLC. All rights reserved. BrightSign and the BrightSign logo are registered trademarks of BrightSign, LLC. Other brand and product names are trademarks or registered trademarks of their respective holders. DOC-08-1

The products shown here are covered by U.S. and/or foreign patent rights. See www.brightsign.biz/patents for more information.