

ZH450

Ultra-Compact High Brightness FHD 1080p Laser Projector



- **Bright FHD 1080p DuraCore laser projector - 4,500 lumens and IP6X certified**
- **Small form factor for easy installation - 1.6x zoom, 360-degree and portrait projection**
- **DuraCore laser technology - 30,000 hours maintenance-free laser light source**
- **Built with the environment in mind - Long laser life span, incorporating Post consumer recycled material**



The ZH450 is Optoma's most compact hassle free FHD 1080p DuraCore laser projector to date. Designed for maintenance-free continuous operation, it can be installed in virtually any orientation and location due to the small and lightweight footprint (34% smaller).

Specifications

EAN: 5055387666825, Colour: White

UPC: 796435 44 659 8, Colour: White

The following specifications are preliminary and subject to change without notice

Display/image

Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	4,500 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3, 16:9
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 140Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.51m ~ 8.18m (20" ~ 322") diagonal

Lamp info

Light source type	Laser
LASER life	30,000 hours

Optical

Throw ratio	1.4:1 ~ 2.24:1
Projection distance	1m - 10m / 39.37" - 393.7"
Zoom	1.6
Zoom type	Manual
Focal length	20.91 ~ 32.62
Native offset	116%

Connectivity

Connections	Inputs 2 x HDMI 2.0 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45
-------------	--

General

Noise level (typical)	32dB
Noise level (max)	34dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-r
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m
Remote control	Card style
Speaker count	1
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	UHDCast Pro

Power

Power supply	100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	119W
Power consumption (max)	173W

Weight and dimensions

Dimensions (W x D x H)	274 x 216 x 114 mm / 10.79" x 8.5" x 4.49"
Gross weight	4.2 kg / 9.26 lbs
Net weight	3 kg / 6.61 lbs

